



1033

TUB 'N TILE ACRYLIC LATEX CAULK WITH SILICONE Data Sheet

DYNAMITE® TUB 'N TILE

- Interior/Exterior
Extra Water Resistance
Flexible Seal

Dynamite® Tub 'N Tile Caulk is a premium acrylic latex formulation for use around tubs, showers, sinks and most any other household application where a flexible, water resistant seal is needed.

FEATURES:

- Acrylic latex formula resists yellowing
Excellent adhesive characteristics
Permanently flexible, long lasting seal

DIRECTIONS:

Clean the surface of residual soap, mildew, loose grout, and old caulk. Rinse the surface thoroughly. Apply caulk when the surface is dry. Trim nozzle to desired bead size. Immediately upon application, bead may be smoothed with a wet finger, sponge or brush.

COVERAGE: Each 10.1 ounce cartridge covers approximately 55 linear feet per 3/16" bead.

TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS

Table with 2 columns: Property and Value. Rows include Color (White), Odor (Mild), Consistency (Smooth Paste), Flash Point (Above 212°F), Vehicle (Acrylic Latex Polymer), Solvent (Water), Pigments (Calcium Carbonate and Titanium Dioxide), Dry To Touch (30 - 60 minutes), Cure Time (5 - 7 Days), % Solids (78% +/- 2%), Recommended Storage Temperature (40 F to 100 F), Recommended Application Range (45 F to 100 F), Service Temperature Range (0 F to 150 F), Shelf Life (12 months).

Approx. Shipping Weights: (Note: All approx. weights include container.)

Table with 2 columns: Quantity and Weight. Rows include 12 - 5.5 fl. oz. tubes/case (7.5 lbs.), 12 - 10 fl. oz. tubes/case (15 lbs.), Cases Per Pallet (140 Cases).

CAUTION! HARMFUL IF SWALLOWED. DO NOT TAKE INTERNALLY. KEEP AWAY FROM CHILDREN.

Avoid breathing vapors, use only in a well ventilated area. Avoid contact with eyes or skin. Seek medical attention if irritation develops. DO NOT STORE OR APPLY AT TEMPERATURES BELOW 40°F.

VOC: less than 1.5% by wt.

INGREDIENTS:

Table with 2 columns: Ingredient and CAS#. Rows include Acrylic Polymer, Calcium Carbonate, Titanium Dioxide, Butyl Benzyl Phthalate, Mineral Spirits, And other additives.

CALIF. PROP. 65 • CHEMICAL WARNING (CALIFORNIA HEALTH AND SAFETY CODE #25249.5 ET SEQ). WARNING: This product contains chemicals known to the State of California to cause cancer.

LIMITED LIFETIME WARRANTY:

We guarantee that if you use Dynamite Siliconized Acrylic Latex Tub 'N Tile Caulk as directed and it fails to perform as is indicated on this label, Sealant Technology will provide you with a free replacement cartridge.

©2006 Sealant Technology, Inc. Manufactured by Sealant Technology P.O. Box 5449, Tampa, FL 33675 A division of Gardner-Gibson, Inc.

See MSDS for more info

Sealant Technology, A Division of Gardner-Gibson, Inc. • P.O. Box 5449 • Tampa, Florida 33675-5449 Phone: (813) 248-2101 • Fax (813) 248-6768 • www.sealanttechnology.com, www.gardner-gibson.com

